

STATE ENGINEER OFFICE
WELL RECORD

Section 1. GENERAL INFORMATION

(A) Owner of well William A Vest 71E and his wife Kathrine L Vest Owner's Well No. _____
Street or Post Office Address P.O. Box 820
City and State Manahat de Taus NM 87557

Well was drilled under Permit No. TPG 74812 and is located in the:

a. _____ N _____ W _____ W _____ E of Section _____ Township _____ Range _____ N.M.P.S.
b. Tract No. _____ of Map No. _____ of the _____
c. Lot No. _____ of Block No. _____ of the _____
Subdivision, recorded in _____ County.
d. X = 701,840 feet, Y = 1,959,700 feet, N.M. Coordinate System Central Zone in
the Manahat de Taus Taus County Grant.

(B) Drilling Contractor Fennell Drilling Co License No. WD 987
Address P.O. Box 480 Arroyo Hondo NM 87513

Drilling Began NA Completed NA Type tools _____ Size of hole ? in.
Elevation of land surface or _____ at well is _____ ft. Total depth of well 120 ft.
Completed well is shallow artesian. Depth to water upon completion of well 64' ft.

Section 2. PRINCIPAL WATER-BEARING STRATA

Depth in Feet		Thickness in Feet	Description of Water-Bearing Formation	Estimated Yield (gallons per minute)
From	To			
			<u>see Remarks on Page</u>	

Section 3. RECORD OF CASING

Diameter (inches)	Pounds per foot	Threads per in.	Depth in Feet		Length (feet)	Type of Shoe	Perforations	
			Top	Bottom			From	To
<u>6 5/8</u>	<u>13.</u>		<u>0</u>	<u>120</u>	<u>120</u>			

Section 4. RECORD OF MUDDING AND CEMENTING

Depth in Feet		Hole Diameter	Sacks of Mud	Cubic Feet of Cement	Method of Placement
From	To				
<u>NA</u>					

Section 5. PLUGGING RECORD

Plugging Contractor _____
Address _____
Plugging Method _____
Date Well Plugged _____
Plugging approved by: _____
State Engineer Representative

No.	Depth in Feet		Cubic Feet of Cement
	Top	Bottom	
1			
2			
3			
4			

Date Received 4-3-01

FOR USE OF STATE ENGINEER ONLY

File No. RG 74812

Quad _____ FWL _____ FSL _____

Use DOM Location No. _____

OFFICE OF STATE ENGINEER
SANTA FE, NEW MEXICO
2003 DEC 15 PM 12:46

01 APR 2001 11:51 AM

Section 6. LOG OF HOLE

Depth in Feet		Thickness in Feet	Color and Type of Material Encountered
From	To		
			NA

Section 7. REMARKS AND ADDITIONAL INFORMATION

To State Engineer:
Fennell Drilling Test Pumped the existing well at 20 gpm @ with adro down of 2' - no other action was taken

Jim I Fennell

The undersigned hereby certifies that, to the best of his knowledge and belief, the foregoing is a true and correct record of the above described hole.

Jim I Fennell
Driller

INSTRUCTIONS: This form should be executed in triplicate, preferably typewritten, and submitted to the appropriate district office of the State Engineer. All sections, except Section 5, shall be answered as completely and accurately as possible when any well is drilled, repaired or deepened. When this form is used as a plugging record, only Section 1(a) and Section 5 need be completed.

STATE ENGINEER OFFICE
WELL RECORD

191177

Section 1. GENERAL INFORMATION

(A) Owner of well William A Yost III & wife Katherine Yost Owner's Well No. _____
Street or Post Office Address P.O. Box 820
City and State Fernando de Taos NM 87557

Well was drilled under Permit No. PG 74812 and is located in the:

- a. _____ 1/4 _____ 1/4 _____ 1/4 _____ 1/4 of Section _____ Township _____ Range _____ N.M.P.N.
b. Tract No. _____ of Map No. _____ of the _____
c. Lot No. _____ of Block No. _____ of the _____
Subdivision, recorded in _____ County.
d. X= 701,840 feet, Y= 1,959,700 feet, N.M. Coordinate System central Zone in
the Fernando de Taos (Taos County) Grant.

(B) Drilling Contractor Fennell Drilling Co License No. W D 987

Address P.O. Box 480 Arroyo Hondo NM 87513

Drilling Began 11-21-00 Completed 11-22-00 Type tools rotary Size of hole 7/8 in.

Elevation of land surface or _____ at well is _____ ft. Total depth of well 200 ft.

Completed well is shallow artesian. Depth to water upon completion of well 62 ft.

Section 2. PRINCIPAL WATER-BEARING STRATA

Depth in Feet		Thickness in Feet	Description of Water-Bearing Formation	Estimated Yield (gallons per minute)
From	To			
<u>140</u>	<u>200</u>	<u>60</u>	<u>sand & gravel</u>	<u>30+</u>

Section 3. RECORD OF CASING

Diameter (inches)	Pounds per foot	Threads per in.	Depth in Feet		Length (feet)	Type of Shoe	Perforations	
			Top	Bottom			From	To
<u>5 1/2"</u>	<u>PVC</u>		<u>0</u>	<u>200</u>	<u>200</u>		<u>140</u>	<u>200</u>

Section 4. RECORD OF MUDDING AND CEMENTING

Depth in Feet		Hole Diameter	Sacks of Mud	Cubic Feet of Cement	Method of Placement
From	To				
<u>0</u>	<u>20</u>	<u>7/8</u>	<u>3 Bags of Bestmix</u>	<u>obius</u>	<u>grout</u>

Section 5. PLUGGING RECORD

Plugging Contractor _____
Address _____
Plugging Method _____
Date Well Plugged _____
Plugging approved by: _____

State Engineer Representative

No.	Depth in Feet		Cubic Feet of Cement
	Top	Bottom	
<u>1</u>			
<u>2</u>			
<u>3</u>			
<u>4</u>			

STATE ENGINEER OFFICE
 ALBUQUERQUE
 NOV 28 4 19 PM '00

Date Received 11-28-2000 FOR USE OF STATE ENGINEER ONLY Fernando de Taos

File No. RG 74812 Use Dam Location No. X 701 840 / 1959700
central

Depth in Feet		Thickness in Feet	Color and Type of Material Encountered
From	To		
0	10	10	clay
10	25	15	sand & gravel
25	140	115	sand, clay & gravel with cobbles
140	200	60	sand & gravel

Section 7. REMARKS AND ADDITIONAL INFORMATION

The undersigned hereby certifies that, to the best of his knowledge and belief, the foregoing is a true and correct record of the above described hole.


Driller

INSTRUCTIONS: This form should be executed in triplicate, preferably typewritten, and submitted to the appropriate district office of the State Engineer. All sections, except Section 5, shall be answered as completely and accurately as possible when any well is drilled, repaired or deepened. When this form is used as a plugging record, only Section 1(a) and Section 5 need be completed.